

Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Manual Ratchet Threaders



Product Description

 All matched Threader/Sets including Die Heads, Ratchet Assembly, Ratchet and Alloy Dies. Different Threader Sets maybe use different Dies and Head, consult us when you choosing.

Ratchet Lever

Convenient, lockable reversal of ratchet direction

Quick adjustment

 Secure hold with retainer locking, simple insertion and removal of die heads

User friendly

Slim, compact shape with excellent overall size, angle requirements of 22.5°

For easy work in difficult to reach positions

 Ratchet Assembly and long lever Labor saving

Quick Change Die Heads

- Positive octagonal universal drive with retainer locking
 Secure hold
- Long pipe guide

Perfect centering

Simple insertion and removal of die heads

Easy changing

Precision Dies

- High-quality tempered steel
- Optimised cutting geometry


Ordering Information

Catalog No.		Model No.	Capacity		N.W
BSPT	NPT	Model No.	in.	mm	kg
602210	602209	HL-12R	1/2-2	12-50	25



TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: www.pipetool.com.cn

Page 1 of 7



Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Manual Ratchet Threader With Carrying Case





Catalog No.		M. J. IN.	Capacity		N.W
BSPT	NPT	Model No.	in.	mm	kg
4511010	4511011	HL-62D	1/4-11/4	6-32	6.5
4511012	4511013	HL-62D	3/8-11/4	10-32	6
4511014	4511015	HL-62D	1/2-11/4	12-32	5.5





Catalog No.		Model No.	Capacity		N.W
BSPT	NPT	iviodel No.	in.	mm	kg
4511110	4511111	HL-62B	1/2-11/4	12-32	4.5






Catal	og No.	Model No	Сара	acity	N.W
BSPT	NPT	- Model No.	in.	mm	kg
4511210	4511211	HL-62	1/4-11/4	6-32	6.25
4511212	4511213	HL-62	3/8-11/4	10-32	5.5
4511214	4511215	HL-62	1/2-11/4	12-32	4.75
4511216	4511217	HL-62	1/2-1	12-25	4



TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: <u>www.pipetool.com.cn</u>

Page 2 of 7



Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Manual Ratchet Threader With Carrying Case





Catalog No.	Model No.	Capacity	N.W	
metric	Widdel No.	Сарасіту	kg	
45112010	HL-62M	M16 – M32	4	





Catalog No.		MadalNa	Capacity		N.W
BSPT	NPT	Model No.	in.	mm	kg
4511310	4511311	HL-63	3/8-2	10-50	12.5
4511312	4511313	HL-63	<i>Y</i> 2-2	12-50	12






Catal	Catalog No. Model No.		Сар	Capacity	
BSPT	NPT	- Model No	in.	mm	kg
4511314	4511315	HL-63	11/4-2	32-50	9
4511316	4511317	HL-63	1½-2	40-50	8



TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: www.pipetool.com.cn

Page 3 of 7



Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Manual Ratchet Threader With Carrying Case





Catalog No.	Model No.	Сар	Capacity	
BSPT	Woder No.	in.	mm	kg
4511510	HL-112	<i>Y</i> ₂ -1 <i>Y</i> ₄	12-32	3.5





Catalog No.		Model No.	Capacity		The state of the s	N.W
BSPT	NPT	- Woder No.	in.	mm	kg	
4512210	4512211	HL-114	1/2-2	12-50	8	






Catal	og No.	Madel No	Capacity		N.W
BSPT	NPT	Model No.	in.	mm	kg
4512310	4512311	HL-117	2 1/2-4	62-100	21

012 **HONG LI**

TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: www.pipetool.com.cn

Page 4 of 7



Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Power Drive





Product Description

 The Model HSQ50 power drive, constructed with a rugged cast aluminum housing, is designed for heavy-duty applications and daily use. It is ideal for mechanical, electrical and plumbing jobs. HSQ50 can be used to actuate pipe cutter, geared threader etc.

Specifications

- Motor: Universal, 1500W
- Speed: 32RPM (no load)
- Gear head: All Spur-gear Reduction.

Spring-loaded Adapter Pawl.

- Body: Hardened Steel Spindle Gear
 - Gear Case, Motor Housing and Handle are Cast Aluminum.
- Threading Capacity: 1/2"-2" (die heads to order separately)
- Length: 72cm



Ordering Information


Catalog No.	Model No.	Description	N.W(kg)
306301	HSQ50	Power drive 110V-60Hz	20
306302	HSQ50	Power drive 220V-50Hz	20





TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: www.pipetool.com.cn

Page 5 of 7



Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Nipple Chuck



819 Nipple Chuck Kit

- Holds short or close nipples for threading.
- For use with SQ50B1, SQ50C1, SQ80D, SQ80D1, SQ100D, SQ100D1, SQ50A, SQ80A, SQ100A, SQ50, SQ50D, SQ50E, SQ50F, SQ80C1, SQ100F.
- Standard Nipple Chuck includes insert and 5 adapters: ½", ¾", 1", 1¼", and 1½". (Nipple Chuck body serves as 2" Adapter.)

Ordering Information

Catalog No. Model No.		Description	Pipe Capacity		N.W(kg)
Catalog No. Woder No.	Description	(in)	(mm)	14.44(Kg)	
4581011	819	NPT Nipple Chuck	1/2-2	12-50	4.5
4581010	819	BSPT Nipple Chuck	1/2-2	12-50	4.5





Oiler



Product Description

- To work with portable threaders or other manual oilling required applications.
- Oil is filtered and recirculated through reservior.
- An ergonomic 2-finger trigger design that reduces user fatigue.

Ordering Information


Catalog No.	Model No.	Description	N.W (kg)
11102001		Oiler Complete	5
11102004		Oiler Gun with Hose	2





TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: www.pipetool.com.cn

Page 6 of 7



Practical Reliable Outstanding

SPECIALIZED IN PIPELINE CONNECTION

THREADING AND GROOVING

Portable Threading Machine





Product Description

• The SQ30-2B is a light weight and powerful portable threader. It is designed for threading ½"-2" pipe with 11-R Die Heads. The SQ30-2B is equipped with a full set of 11-R Die Heads, ½"-2", the SQ30-2B Support Arm and a durable Carrying Case. The SQ30-2B Power Drive is the perfect portable power drive for maintance and repair workers, as well as service plumbers requiring 2" pipe capacity.

Specifications

- Capacity: ½"-2" (15mm-50mm) pipe
- Motor: 1350W Universal 110V or 220V, 50/60Hz.
- Switch: Heavy-duty paddle-type switch with safety lock off device (automatically locks off when released). Separate mechanical transmission FOR/REV switch. Reverse 3-times faster than threading.
- Gear Head: Spur gear reduction/ring gear drive. All shafts, ball and needle bearing mounted. Permanently lubricated gear housing.
- . Gear Housing: Die cast Aluminum.
- Body & Handle: Durable heavy-duty fiberglass reinforced plastic.
- Spindle Speed: 28 RPM for threading, 51 RPM reverse (No load)
- Die Heads: ½", ¾", 1", 1¼", 1½", 2" (Type 11R)
- Includes support arm.
- Screw Threads: NPT / BSPT
- Dies Material: Alloy standard, (HSS optional)
- Die Head Adapter: Used with 1/2" through 11/4" die heads.
- weight: 8 kg, power drive only.
- Length: 76 cm
- . Approved by CSA and CE strandards



Model SQ30-2B operating

Model SQ30-2B with Support Arm, Die Heads and Carrying Case

Operation in close quaters

Ordering Information

Catalog No.	Model No.	Description	N.W(kg)
306202	SQ30-2B	110V 1/2"-2" NPT w/Case and Support Arm	22
306201	SQ30-2B	220V 1/2"-2" BSPT w/Case and Support Arm	22
Accessories			
30111028		Adapter	0.65
11101002		Support Arm	
11102001		Oiler (optional)	5
602201	H401	1/8"-6" TRISTAND chain vise (optional)	20



TEL: 0086-571-86260006 FAX: 0086-571-86260893 WEB: www.pipetool.com.cn